

HOLLAND HYDRAULIC 68 OIL

ITEM NUMBER: HH1068 | ISO-VG 68 | MINERAL

Hydraulic 68 is a high-performance hydraulic fluid for heavy-duty mobile and stationary hydraulic systems operating under high pressures and across a wide temperature range. It is suitable for systems where limited water ingress may occur and can also be used in circulating lubrication systems, general lubrication applications and vacuum pumps, excluding turbines. Suitable for systems containing silver components.



APPLICATIONS

Holland Hydraulic 68 is a high-performance EP hydraulic oil formulated with carefully selected solvent-refined base oils and advanced additives. It provides reliable performance, viscosity stability and effective protection under demanding operating conditions.

PERFORMANCE LEVELS

- // AFNOR NF E 48-603
- // Denison HF-2
- // DIN 51524-2 HLP
- // Eaton (Vickers) 1-286-S
- // SEB 181222
- // US Steel 127

TECHNICAL SPECIFICATIONS

Density at 15 °C	kg/l	0,882
Viscosity 40 °C	mm ² /s	68
Viscosity 100 °C	mm ² /s.	8,80
Viscosity Index	-	102
Flash Point COC	°C	220
Pour Point	°C	-24
Acid number	mgKOH/g	0,40
Sulphate Ash	%	0,06