

ZF8 GUARDMATIC FLUID

Fully synthetic lubricant formulated with selected base oils, developed for use in ZF 6-, 8- and 9-speed automatic transmissions.

The formulation supports stable operation across a wide range of temperatures and operating conditions. It provides consistent friction characteristics, ensuring smooth gear shifting and supporting long-term transmission performance.



APPLICATIONS

For use in automatic transmissions requiring fluids for ZF 6-, 8- and 9-speed gearboxes, as applied in a wide range of European, Asian and American vehicles. Suitable for service, maintenance and refill operations in accordance with manufacturer specifications. The formulation is developed to maintain consistent friction behaviour over time, supporting smooth shifting performance and stable operation throughout the service interval.

TECHNICAL SPECIFICATIONS

COLOR		GREEN
Density at 15 °C	kg/l	0.845
Viscosity 40 °C	mm ² /s	28.1
Viscosity 100 °C	mm ² /s.	5.94
Brookfield viscosity at -40°C	mPas	9500
Viscosity Index	-	164
Flash Point COC	°C	210
Pour Point	°C	-48

PERFORMANCE LEVELS

- // ZF 8 HP
- // ACURA 08200-9016a
- // ACURA ATF TYPE 3.0
- // ATF L 12108
- // BMW: 83222152426
- // BMW: 83225A12A00
- // BMW: 83222305397
- // CHRYSLER: 68157995AA
- // FIAT: 9.55550-AV5
- // HONDA 8200-9017
- // HONDA ATF TYPE 3.1
- // JAGUAR: 02JDE26444
- // LAND ROVER: LR023288
- // LAND ROVER: LR023289
- // VW G 055 162
- // VW 060 162
- // ZF S671 090 312
- // ZF TE-ML 11

