

HOLLAND HYDRAULIC 46 OIL

ITEM NUMBER: HH1046 | ISO-VG 46 | MINERAL

Holland Hydraulic 46 is suitable for heavy-duty hydraulic systems in both mobile and industrial equipment operating under demanding conditions. It may also be used in light-duty gearboxes, bearings and circulating lubrication systems where a reliable hydraulic oil is required. Additional applications include general lubrication and vacuum pumps, excluding turbine applications.



APPLICATIONS

Our Hydraulic 46 is suitable for industrial and mobile hydraulic systems operating under demanding conditions. It may also be used in light-duty gearboxes, bearings, lubrication systems and vacuum pumps, excluding turbines.

PERFORMANCE LEVELS

- // AFNOR NF E 48-603
- // Denison HF-2
- // DIN 51524-2 HLP
- // Eaton (Vickers) 1-286-S
- // ISO 6743-4 HM
- // SEB 181222
- // US Steel 127

TECHNICAL SPECIFICATIONS

Density at 15 °C	kg/l	0,870
Viscosity 40 °C	mm ² /s	46,00
Viscosity 100 °C	mm ² /s.	6,97
Viscosity Index	-	108
Flash Point COC	°C	215
Pour Point	°C	-30
Acid number	mgKOH/g	0,40
Sulphate Ash	%	0,06