

5W-30 PRO-TECT | HV10001

A fully synthetic mid-SAPS engine oil. It is formulated to provide protection against wear and corrosion and is suitable for use in modern passenger vehicles equipped with diesel particulate filters (DPF) and/or catalytic converters..



APPLICATIONS

5W-30 is a universal synthetic engine oil suitable for petrol and diesel engines, with or without turbocharging. It is also suitable for passenger car diesel engines equipped with pump-injector systems. Due to compliance with multiple manufacturer requirements, this product has a wide range of applications.

TECHNICAL SPECIFICATIONS

Density at 15 °C	kg/l	0,851
Viscositeit -30 °C	mPa.s	6050
Viscosity 40 °C	mm ² /s	71,50
Viscosity 100 °C	mm ² /s.	12,40
Viscosity Index	-	173
Flash Point COC	°C	215
Pour Point	°C	-36 °C
Total Base Number	mgKOH/g	7,4
Sulphated Ash Content	%	0,78

PERFORMANCE LEVELS

- // ACEA C3
- // API SN/CF
- // MB 229.31/229.51/229.52/226.52
- // BMW Longlife-04
- // Opel OV 040 1547 - D30
- // VW 502.00/505.00/501.01
- // GM dexos D
- // GM dexos 2
- // Opel GM-LL-B-025
- // Fiat 9.55535-S3