

15W-40 EURO SHIELD | HT10007

EURO SHIELD 15W-40 is a high-performance mineral engine oil developed for heavy-duty diesel engines. Its advanced additive system provides reliable protection against wear, deposits and oxidation, even under demanding operating conditions.



APPLICATIONS

Suitable for naturally aspirated and turbocharged diesel and petrol engines, particularly in trucks, commercial vehicles and mixed fleets. Designed for use in Euro 4 and Euro 5 engines where the specified performance levels are required.

TECHNICAL SPECIFICATIONS

Density at 15 °C	kg/l	0,878
Viscositeit -20 °C	mPa.s	5180
Viscositeit 40 °C	mm²/s	98,00
Viscosity 100 °C	mm²/s.	13,60
Viscosity Index	-	134
Flash Point COC	°C	212
Pour Point	°C	-36
Total Base Number	mgKOH/g	11,1
Sulphate Ash	%	1,43

OFFICIALLY APPROVED

- // Volvo VDS-3
- // Mack EO-N
- // Renault RLD-2

PERFORMANCE LEVELS

- // ACEA E7
- // API CI-4/SL
- // MB 228.3
- // Volvo VDS-3
- // Renault RLD-2
- // Mack EO-N
- // MAN M 3275
- // Renault RLD
- // CAT ECF-1-a/ECF-2
- // Cummins CES
20076/20077/20078
- // Deutz DQC III-10
- // Global DHD-1
- // MTU Type 2
- // Detroit Diesel DDC 93K215
- // Mack EO-M Plus