

15W-40 EURO MOTION | HT10006

EURO MOTION 15W-40 is a high-performance Mid SAPS engine oil developed for modern heavy-duty diesel engines. It provides excellent protection against wear, oxidation and deposits while supporting low-emission exhaust systems.



APPLICATIONS

Suitable for on-road and off-road diesel engines, including Euro 5 and Euro 6 vehicles equipped with SCR systems. It can also be used in selected Euro 3 and Euro 4 engines where the required specifications are prescribed.

TECHNICAL SPECIFICATIONS

Density at 15 °C	kg/l	0,870
Viscositeit 40 °C	mm ² /s	115
Viscosity 100 °C	mm ² /s.	15,4
Viscosity Index	-	141
Flash Point COC	°C	210
Pour Point	°C	-40
Total Base Number	mgKOH/g	10.0
Sulphate Ash	%	1,0

PERFORMANCE LEVELS

- // ACEA E7
- // ACEA E11
- // API CK-4
- // API CI-4
- // CAT ECF-3
- // Detroit Diesel DFS 93K222
- // DAF E9
- // JASO DH-2
- // Daimler Trucks DTFR 15C100
- // MB 228.31
- // Renault RLD-3
- // Ford WSS-M2C171-F1
- // Mack EO-S premium plus
- // Cummins CES 20086/20081
- // Deutz DQC III-18 LA
- // MAN M 3775
- // MTU Type 2.1
- // Volvo VDS-4.5