

20W-50 EUROMAX | ENGINE OIL

20W-50 is a high-quality mineral-based heavy-duty engine oil, formulated with premium additives to maintain a stable viscosity index and provide reliable engine protection under demanding operating conditions.



APPLICATIONS

Holland 20W-50 is suitable for both petrol and diesel engines, with or without a turbocharger, operating under the most demanding conditions in all seasons. Thanks to its specially formulated additive package, it is also suitable for use with diesel fuels containing relatively high levels of sulphur. This product is suitable for use in Euro 4 and Euro 5 engines.

TECHNICAL SPECIFICATIONS

Density at 15 °C	kg/l	0,888
Viscosity -20 °C	mPa.s	7600
Viscosity 40 °C	mm²/s	154,30
Viscosity 100 °C	mm²/s.	17,3
Viscosity Index	-	122
Flash Point COC	°C	226
Pour Point	°C	-30
Total Base Number	mgKOH/g	11
Sulphated Ash Content	%	1,43

PERFORMANCE LEVELS

- // ACEA E7
- // API SL/CI-4
- // Volvo VDS-3
- // CAT ECF-1-a/ECF-2
- // MAN 3275-1
- // MB 228.3
- // Renault VI RLD-2
- // Cummins CES 20077/20078
- // Detroit Diesel 93K215
- // Deutz DQC III-10
- // Global DHD-1
- // Mack EO-N/EO-M Plus
- // MTU Type 2
- // JASO DH-1
- // MAN M 3275-1