

HOLLAND GREASE EP2

LITHIUM MINERAL | NLGI 2

EP2 is suitable for a wide range of industrial and automotive lubrication applications. It can be used for bearings, chassis components and other grease-lubricated parts operating under moderate to heavy loads, provided the application remains within the recommended operating temperature range.

- Excellent mechanical stability
- High load-carrying capability
- Protection against corrosion



PERFORMANCE LEVELS

// ISO 6743: ISO-L-XCCFB2

// DIN 51502: KP2K-30

TYPICALS

Colour	Light brown
Base fluid	Mineral oil
Thickener	Lithium
NLGI Grade (ASTM D217)	2
Dropping point, °C (IP 396)	>180
Viscosity 40°C, mm²/s (base oil)	280
Viscosity 100°C, mm²/s (base oil)	20
Penetration 60 strokes (ISO 2137)	265 – 295 (60 str) +35 (100.000 str)
4-ball weld load (DIN 51350:4)	2600N
Water resist. 90°C (DIN 51807:1)	1
Water resist. 80°C (ISO 11009)	8%
Emcor dist water (ISO 11007)	0 – 0 (dist) 2 – 2 (salt)
Copper corrosion (ASTM D4048)	1b
SKF R2F A+B	P
Oxidation stability 100h/100 °C (ASTM D942)	20kPa
Flow pressure -30 °C (DIN 51805)	<1400hPa
Density (IPPM-CS/03 530)	0,91
Temperature range	-30 to +120°C (max 130°C)

