

HOLLAND HYDRAULIC 32 OIL

ITEM NUMBER: HH1032 | ISO-VG 32 | MINERAL

Holland Hydraulic 32 is a high-quality EP hydraulic oil formulated with carefully selected solvent-refined base oils and a balanced additive system. It provides reliable performance, viscosity stability and effective protection for hydraulic systems operating under demanding conditions.



APPLICATIONS

Holland Hydraulic 32 is suitable for heavy-duty hydraulic systems in both mobile and industrial equipment operating under demanding conditions. It may also be used in light-duty gearboxes, bearings and circulating lubrication systems. Additional applications include general lubrication and vacuum pumps, excluding turbine applications.

PERFORMANCE LEVELS

- // AFNOR NF E 48-603
- // Denison HF-2
- // DIN 51524-2 HLP
- // Eaton (Vickers) 1-286-S
- // ISO 6743-4 HM
- // SEB 181222
- // US Steel 127

TECHNICAL SPECIFICATIONS

Density at 15 °C	kg/l	0,850
Viscosity 40 °C	mm ² /s	32,00
Viscosity 100 °C	mm ² /s.	5,52
Viscosity Index	-	108
Flash Point COC	°C	205
Pour Point	°C	-30
Acid number	mgKOH/g	0,40
Sulphate Ash	%	0,06