HOLLAND LUBRICANTS

BEST QUALITY MADE IN THE NETHERLANDS

15W-40 EURO MOTION | HT10009

Mineral multigrade engine oil for petrol and diesel engines, including turbocharged applications. Formulated to maintain a stable viscosity and support reliable protection under demanding use.



APPLICATIONS

For petrol and diesel engines in Euro 4 and Euro 5 applications, with or without turbocharging, including operation with fuels containing relatively high sulphur.

PERFORMANCE LEVELS

- ACEA E7
- API CI-4/SL
- Allison C3
- Cat ECF-1-A / ECF-2 / TO-2
- Cummins CES 20077/20078
- Detroit Diesel DDC 93K215
- Deutz DQC III-18
- ZF 04C / 04P / 07C / 07D / 21K
- Global DHD-1
- JASO DH-1
- Mack EO-M Plus / EO-N
- MAN M 3575-1
- MB 228.3
- MTU Type 2
- Renault RLD / RLD-2
- Volvo VDS-3

TECHNICAL SPECIFICATIONS

Colour	-	Amber
Density at 15 °C	kg/l	0,867
Viscosity -20 °C	mPa.s	6500
Viscosity 40 °C	mm^2/s	98,00
Viscosity 100 °C	mm^2/s	14,40
Viscosity Index	-	147
Flash Point COC	°C	212
Pour Point	°C	-36
Total Base Number	mgKOH/g	11,1
Sulphate Ash	%	1,43

8 721516 684011

GS1

HOLLAND

MADE IN EU THE NETHERLANDS