HOLLAND LUBRICANTS

BEST QUALITY MADE IN THE NETHERLANDS

10W-40 EURO MAX | HT10013

Synthetic low-SAPS multigrade oil for high-speed four-stroke diesel engines. It supports oxidation and shear stability, engine cleanliness and wear protection.



APPLICATIONS

For on-road and off-highway diesel vehicles, including Euro 5 and 6 with SCR, and Euro 3 and 4 engines where specified by the manufacturer.

PERFORMANCE LEVELS

- // ACEA E7/E9
- // API CK-4/CI-4
- // Caterpillar ECF-3
- // Cummins 20086 / 20081
- // Detroit Diesel DDCC 93K222
- // Deutz DQC III-10 LA
- // Ford WSS-M2C171-F1
- // JASO DH-2
- // Mack EO-S 4.5
- // MAN M 3575
- // MB 228.31
- // MTU Type 2.1
- // Renault RLD-4 / RLD-3
- // Volvo VDS-4.5 / VDS-4

TECHNICAL SPECIFICATIONS

Density at 15 °C	kg/l	0,870
Viscosity -25 °C	mPa.s	6510
Viscosity 40 °C	mm²/s	81,20
Viscosity 100 °C	mm²/s	12,00
Viscosity Index	-	142
Flash Point COC	°C	228
Pour Point	°C	-39
Total Base Number	mgKOH/g	10,0
Sulphated Ash	%	1,00

8 721516 684011

GS1

HOLLAND

MADE IN EU THE NETHERLANDS