HOLLAND LUBRICANTS

BEST QUALITY MADE IN THE NETHERLANDS

20W-50 EURO MOTION | HT10016

Mineral multigrade engine oil for petrol and diesel engines. A balanced additive system provides a stable viscosity and supports protection in demanding service.



APPLICATIONS

For naturally aspirated or turbocharged petrol and diesel engines, including Euro 4 and Euro 5 applications and use with relatively high-sulphur fuels.

PERFORMANCE LEVELS

- // ACEA E7
- // API SL/CI-4
- // Cat ECF-1-a/ECF-2
- // Cummins CES 20077/20078
- // Deutz DQC III-10
- // Detroit Diesel 93K215
- // Global DHD-1
- // JASO DH-1
- // Mack EO-N/EO-M Plus
- // MAN 3275-1
- // MB 228.3
- // MTU Type 2
- // Renault VI RLD-2
- // Volvo VDS-3

TECHNICAL SPECIFICATIONS

Density at 15 °C	kg/l	0,888
Viscosity -15 °C	mPa.s	7500
Viscosity 40 °C	mm²/s	156,30
Viscosity 100 °C	mm²/s	17,50
Viscosity Index	-	123
Flash Point COC	°C	230
Pour Point	°C	-30
Total Base Number	mgKOH/g	11,1
Sulphate Ash	%	1,43

8 721516 684011

GS1

HOLLAND

MADE IN EU THE NETHERLANDS