HOLLAND LUBRICANTS

BEST QUALITY MADE IN THE NETHERLANDS

5W-30 EURO TITAN | HT10014

Fully synthetic low-SAPS diesel engine oil developed for fuel-efficient operation. Its additive system helps control deposits and sludge while protecting against wear.



APPLICATIONS

For demanding Euro 5 and Euro 6 diesel engines using low-sulphur fuel, including vehicles fitted with particulate filters or exhaust gas catalysts.

PERFORMANCE LEVELS

- ACEA E6/E7/E9/E11
- API CK-4
- Cat ECF-3
- Cummins 20081 / 20086
- Deutz DQC IV-18 LA
- DTFR 15C120 / 15C110 / 15C100
- Detroit Diesel DFS 93K222
- JASO DH-2
- Mack EO-S 4.5
- MAN M 3677 / M 3477
- MB 228.51 / 228.31
- MTU Type 2.1
- Renault RLD-3 / RGD / RLD-2
- Scania LDF-4 / Low Ash
- Volvo VDS-4.5 / VDS-4 / VDS-3
- Voith Class B

TECHNICAL SPECIFICATIONS

Colour	-	Amber
Density at 15 °C	kg/l	0,855
Viscosity -30 °C	mPa.s	6460
Viscosity 40 °C	mm²/s	70,20
Viscosity 100 °C	mm²/s	11,80
Viscosity Index	-	165
Flash Point COC	°C	214
Pour Point	°C	-45
Total Base Number	mgKOH/g	9,3
Sulphate Ash	%	0,99

8 721516 684011

GS1

HOLLAND

MADE IN EU THE NETHERLANDS